



SOFT METALLIC HEAT TRANSFER MATERIAL FEATURES A DISTINCT LUSTER AND SHINE

Creates a soft, metallised finish for textile decoration. It is supplied on a self-adhesive polyester carrier



AVAILABLE IN

50 cm x 10 m rolls

RECOMMENDED FABRICS

- 100% Cotton
- 100% Polyester
- Polyester-Cotton blends

* Test before application!

CUTTING NOTES

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as the blade ages. For optimal cutting and weeding, maintain a line thickness of at least 1.5 mm (1/16") for lettering and logos.

APPLICATION INSTRUCTIONS

- Temperature: 150° C
- Time: 10 sec.
- Pressure: Medium (#4-6 on Hotronix®)
- Peel: Cold

MULTI-COLOR DESIGNS

Apply background for 2-4 seconds, peel carrier warm/cold. Repeat for additional colors. Finish with final application of 13-15 seconds. Peel cold.

ACCESSORIES RECOMMENDED

- Grip Cover Sheet
- Cover Sheet - Non-Sticky
- EZ Weeder®, LED Weeder. LED Pin or Tweezers

CARE INSTRUCTIONS

Machine wash up to 40° C using mild detergent. Do not use bleach. Do not dry-clean. Do not iron directly onto CAD-CUT® Soft Metallic (use cover sheet).

STORAGE

Store in cool, dry area. Avoid direct heat, sunlight and humidity.

DETAILS



KEY

Easy weed	Thin
Ironable	Sticky carrier
Ironable only inside out	Multi-color application
Washable	Peel hot
Sublimation	Application
Stretchable	Pressure
Flock	

CAD-CUT® SOFT METALLIC



5200
red



5201
holo red



5255
light pink



5252
rose pink



5250
hot pink



5280
purple



5320
light blue



5350
navy



5321
light goldish
blue



5400
kelly green



5116
bronze



5550
brown



5815
silver



5115
gold



5700
black